Foam Equipment Catalog 2007





0

What sanitation method gives the best results?



Santoprene or Viton pumps 15° fan tip for increased coverage

25 foot coiled dual tube hose

3-5 cfm at 30-40 psi

Favorable Foam Products Mean Lower Labor Costs

Operator of Equipment Gets Visual Identification of Coverage

An Extended Contact Time Means Maximum Effectiveness

More Versatility Means More Choices

910 Portable (Pre-mix) 25 feet of foam distance 20 foot foam hose 6" fill cap makes filling easy 25 gallon capacity Ergonomic design featuring 4 wheels Drain feature allows for easy emptying 30 foot foam hose 8" fill cap makes filling easy 15 gallon capacity 25 feet of foam distance 30 foot foam hose 8" fill cap makes filling easy 15 gallon capacity 25 feet of foam distance 30 foot foam hose 5-10 cfm at 40-80 psi Stainless steel cart Draws from chemical concentrate 12" x 5" potential area coverage (Pre-mix) 2000-WALL (Pr	Markets serviced with foam		Spe	ecific	ations
Portable (Pre-mix) 915 Portable (Pre-mix) 916 Portable (Pre-mix) 917 Portable (Pre-mix) 918 Portable (Pre-mix) 919 Portable (Pre-mix) 919 Portable (Pre-mix) 910-DS4 Portable (Pre-mix) 900-DS4 Portable (Pre-mix) Poortable (Pre-mix) Poortable (Pre-mix) 900-DS4 Poortable (Pre-mix) Poortable Fogger (Pre-mix) Poo				Portable	25 feet of foam distance 20 foot foam hose
900-DS4 Portable (Pre-mix) Portable Fogger (Pre-mix) Porta			925		Ergonomic design featuring 4 wheels Drain feature allows for easy emptying 30 foot foam hose
900-DS4 Wall Mount Doorway (Concentrate) 900-WALL Wall (Pre-mix) 900-WC Wall (Concentrate) 900-WC Portable Fogger (Pre-mix) 900-PU Pump-up (Pre-mix) 900-PU Pump-up (Pre-mix) Pump-up (Pre-mix) Pump-up (Pre-mix) Glass filled polypro foam wand	Industrial	9	915		25 feet of foam distance 30 foot foam hose 5-10 cfm at 40-80 psi
900-WALL Wall (Pre-mix) 900-WC Wall (Concentrate) 900-FOG Portable Fogger (Pre-mix) Pump-up (Pre-mix) 900-2PU Pump-up (Pre-mix) 900-WC Wall (Concentrate) 30 gallons of foam per minute Up to 25 feet of foam distance 50 foot foam per minute Up to 25 feet of foam distance 50 foot foam per minute Up to 25 feet of foam per minute Up to 25 feet of foam distance 50 foot foam per minute Up to 25 feet of foam distance 30 gallons of foam per minute Up to 25 feet of foam distance 50 foot foam per minute Up to 25 feet of foam distance 30 gallons of foam per minute Up to 25 feet of foam distance 10 gallon per minute Up to 25 feet of foam distance 10 gallon per minute Up to 25 feet of foam distance 10 gallon per minute Up to 25 feet of foam distance 10 gallon per minute Up to 25 feet of foam distance 10 gallon per minute Up to 25 feet of foam distance 10 gallon so feet of foam distance 10 gallon so foam per minute Up to 25 feet of foam distance 10 gallon so feet of foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so foam per minute 10 power foam distance 10 gallon so fo		-	900-DS4	Doorway	12' x 5' potential area coverage
900-WC Wall (Concentrate) 910-FOG Portable Fogger (Pre-mix) Pump-up (Pre-mix) Pump-up (Pre-mix) 900-2PU Pump-up (Pre-mix) Pump-up (Pre-mix) 2 gallon capacity 15° fan tip for increased coverage Dual polyurethane tubing Glass filled polypro foam wand		O ®	900-WALL		30 gallons of foam per minute Up to 25 feet of foam distance 50 foot foam hose
910-FOG Portable Fogger (Pre-mix) 900-2PU Pump-up (Pre-mix) Pump-up (Pre-mix) Pump-up (Pre-mix) Glass filled polypro foam wand	FOOd End Beverage	O P	900-WC		30 gallons of foam per minute Up to 25 feet of foam distance 50 foot foam hose
900-2PU Pump-up (Pre-mix) Pump-up (Glass filled polypro foam wand	May May	1	910-FOG		360 degree fog pattern Adjustable telescoping pole 4-8 feet
Contamon of Vitan number	l'emportation		900-2PU		15° fan tip for increased coverage Dual polyurethane tubing Glass filled polypro foam wand Adjustable needle valve for foam control

900-TL

Wall

Portable

DEMA's Portable units operate on compressed air and require only a pre-mixed chemical solution to create thick, long lasting foam. These units come in a variety of cart and tank combinations to meet the foam cleaning requirements of almost all applications and allows the operator to clean faster and more efficiently.

Model 925



Model 910



Model 915



The 925 is a 25 gallon portable foamer that offers innovative new features and ergonomics for industrial and institutional foam cleaning. This unit's four wheel design allows for a wide range of mobility and the convenient drain feature allows for easy emptying.

* Model 950 50 gallon reservoir available

The 910 portable foamer offers an innovative new tank design that allows for easy storage and institutional foam cleaning. The non-pressurized tank promotes safety and consistent foam time after time.

The 915 is a 15 gallon portable foamer that provides thick chemical foam. This unit will allow the operator to clean faster and more efficiently. Ideal for applications requiring a stainless steel cart.

• Doorway • Wall•

DEMA's wall units are available in pre-mix or concentrate models. The pre-mix unit operates on a solution of chemical and water. The concentrate wall unit uses Venturi technology powered by an air pump to ensure consistent water pressure and accurate chemical dilution rates.

Model 900-DS4



The 900-DS4 Doorway sanitizer foaming system allows the control box to be mounted up to 150 feet away from the spray tip assembly. The new foam enhancing nozzle is constructed of Stainless Steel and produces large amounts of foam. This allows for shorter run times and a larger foam coverage area. The 900-DS4 can operate up to three nozzle assemblies simultaneously.

Model 900-WALL



The 900-WALL operates with a pre-mix solution of foaming chemical and water. This unit produces 30 gallons of foam per minute and covers 5-10 cfm at 40-80 psi with up to 25 feet of foam distance.

Model 900-WC



The 900-WC wall concentrate unit eliminates the possibility of water pressure variations by regulating the incoming water pressure and boosting it to the desired pressure level. Consistent water pressure allows the system to produce an accurate chemical dilution level at all times to ensure foam consistency.

• Pump-up • Fog • Wall •

Model 900-2PU



900-2PU pump-up foamer technology provides innovative spot cleaning and sanitation solutions for the industrial and institutional markets. Patented dual tube technology draws the chemical and air from the tank into separate tubes creating thick foam when mixed at the trigger operated foam wand. Flow in the air tube is controlled by a needle valve giving an operator the ability to control foam consistency.

Model 910-FOG



The portable fog unit runs on compressed air, which flows to the fog nozzles where it helps atomize the pre-mixed solution, creating a dense fog. This unit creates a 360 degree pattern for effective fogging in a variety of applications.

Model 900-TL



This wall mount unit operates with a pre-mix solution of foaming chemical and water. Dual hose technology means the operator can start and stop the foam in seconds without degrading foam quality because it is made at the gun. This model is ideal for vehicle washing and detailing.

*Model 900-TLCW provides a second set of hoses and one extra nozzle

Contact Us Today



10020 Big Bend Boulevard St. Louis, Missouri 63122 Telephone: 800-325-3362 Fax: 314-965-8319

Website: www.demaeng.com E-Mail: sales@demaeng.com

DEMA Europe LLC Mast 25, 3891 KE Zeewolde, Netherlands Telephone: 31-(0)-36-522-7006 Fax: 31-(0)-36-522-7863

Website: www.demaeurope.com E-Mail: t.harvey@demaeurope.com

DEMA Australia
Unit 5, 7-11 Parraweena Road
Caringbah N.S.W. 2229
Sydney, Australia

Telephone: 61-2-9525-5177 Fax: 61-2-9525-5033

E-Mail: sales@demaaust.com

DEMA China Representative Office Room 1317, SIPAI Plaza 103 Cao Bao Road Shanghai, 200233 P.R. China Telephone: 86-21-5424-6629

Fax: 86-21-6464-1721

E-Mail: johnzhu@demachina.com.cn

DEMA Latin America São Paulo, Brazil

Telephone: 55-11-39-06-9813

Fax: 55-11-3906-9813

E-Mail: omarp@demaeng.com